



PADDY TIRES

MS955



OFFERING BEST GRIP AND EXCELLENT HANDLING

Design for tractor for soil tillage and spreading in wet soft fields, such as paddy.

SELF-CLEANING AND EXCELLENT WEAR RESISTANCE

Designed to have a wider spacing compared to standard farm tires.

Built with reinforced shoulder walls and made from high-density compounds.

INCREASES EFFICIENCY AND SAVES YOUR MONEY

Designed for Optimal Performance, Durability, and Traction in Agricultural Applications.



MS955

PADDY TIRES

Size	P.R.	Speed-stage load	Type	Rim (Recommendation)	Section Width	Outer Diameter	Pattern Depth		# of lugs	Air pressure	Load
					mm	mm	32nds	mm		kpa	kg
14.9-30	10	A2	TT	W13	378	1560	104.6	83	18x2	260	2410
11-32	6	A2	TT	W10	305	1460	104.6	83	18x2	160	1080
11.2-24	6	A2	TT	W10	285	1205	104.6	83	16x2	210	1465
12.4-26	8	A2	TT	W11	315	1265	92.0	73	17x2	260	2010
16.9-30	10	A2	TT	W15L	430	1585	113.4	90	20x2	200	2455
16.9-34	10	A2	TT	W15L	430	1685	113.4	90	20x2	220	3385
9.5-24	8	A2	TT	W8	240	1150	98.3	78	15x2	310	1420
12.4-24	8	A6	TT	W11	315	1160	40.3	32	19x2	230	1415
8.3-24	8	A6	TT	W7	210	995	32.8	26	18x2	250	830
16.9-30	10	A6	TT	W15L	430	1485	46.6	37	22x2	200	2455
12.4/11-28	6	A2	TT	W11	315	1315	94.5	75	18x2	200	1785
18.4-38	12	A2	TT	W16L	467	1855	113.4	90	19x2	230	3575
7.5-16	6	A2	TT	5.50F	195	890	92.0	73	14x2	300	750
13.6-28	6	A2	TT	W12	345	1370	99.5	79	18x2	190	2000
8.3-24	6	A2	TT	W7	210	1050	93.2	74	15x2	270	1135
8.3-20	6	A2	TT	W7	210	950	93.2	74	14x2	270	970
9.5-20	6	A2	TT	W8	240	1050	98.3	78	14x2	240	1145
13.6-38	10	A2	TT	W12	345	1710	99.5	79	18x2	250	2780
14.9-26	10	A2	TT	W13	387	1460	113.4	90	17x2	230	2040
14.9-28	10	A2	TT	W13	387	1510	113.4	90	17x2	230	2150